

A23c DIN 41612 IDC TYPE FEMALE TRIPLE ROW (A+B+C)

PITCH: 2.54mm * 2.54mm

SPECIFICATIONS


Material

Insulator : PBT, glass reinforced, rated UL 94V-0
 Contact : Phosphor Bronze


Electrical

Current Rating : 1 Amp
 Contact Resistance : 30 mΩ max.
 Insulation Resistance : 3000 MΩ min.
 Dielectric Withstanding Voltage : 500V AC for 1minute
 Operating Temperature : -40°C to +105°C

- ▶ Terminated with L05-0.85mm pitch flat ribbon cable.
- ▶ Mating Suggestion : A23e series.



POSITION	A	B	C	D
48(A+B+C)	55	50	38.10	44.4
96(A+B+C)	95	90	78.74	85.0



How to order: A23c - 1 - 2 - 3 - 4 - 5 - G(RoHS)

1.NO. OF CONTACT	2.CONTACT TYPE	3.CONTACT MATERIAL	4.CONTACT PLATING	5.INSULATOR COLOR
48 96	F: FEMALE	B: PHOSPHOR BRONZE	T: TIN PLATED S: SELECTIVE G: GOLD FLASH A: 5u" INCH GOLD B: 10u" INCH GOLD C: 15u" INCH GOLD D: 30u" INCH GOLD	2. GREY

