

A46a MINI IDC SOCKET (FOR DISCRETE WIRE)

PITCH: 2.54mm * 0.9mm

SPECIFICATIONS








Material

Insulator : PBT, glass reinforced, rated UL 94V-0
 Contact : Phosphor Bronze

Electrical

Current Rating : 1 Amp
 Contact Resistance : 30 mΩ max.
 Insulation Resistance : 3000 MΩ min.
 Dielectric Withstanding Voltage : 500V AC for 1minute
 Operating Temperature : -40°C to +105°C

- ▶ Terminated with UL Style 1061 discrete wire.
- ▶ Mating Suggestion : C85, C85a, C86, C86a series.



How to order: A46a - 1 - 2 - 3 - 4 - 5 - G(RoHS)

1.NO. OF CONTACT	2.CONTACT MATERIAL	3.CONTACT PLATING	4.SPECIAL FUNCTION	5.WIRE SIZE / HOUSING COLOR
02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28	B: PHOSPHOR BRONZE	T: TIN PLATED S: SELECTIVE G: GOLD FLASH A: 5u" INCH GOLD B: 10u" INCH GOLD C: 15u" INCH GOLD D: 30u" INCH GOLD	A: FEED-THRU B: CLOSED END	A: 26 AWG / BLUE B: 28 AWG / GREEN C: 30 AWG / BROWN