

# B41 SINGLE ROW FEMALE HEADER STR (H: 8.4mm)

**PITCH: 2.54mm**



## SPECIFICATIONS

### Material


Insulator : PBT, glass reinforced, rated UL 94V-0  
 Contact : Phosphor Bronze or Brass

### Electrical





Current Rating : 1 Amp  
 Contact Resistance : 30 mΩ max.  
 Insulation Resistance : 3000 MΩ min.  
 Dielectric Withstanding Voltage : 500V AC for 1minute  
 Operating Temperature : -40°C to +105°C  
 ► Mating Suggestion : C69 & C70 series.




(TYPE A)



(TYPE B)



RECOMMENDED P.C.B. LAYOUT



RECOMMENDED P.C.B. LAYOUT

**How to order:** B41 - 1 - 2 - 3 - 4 - 5 - G(RoHS)

1.NO. OF CONTACT	2.CONTACT MATERIAL	3.CONTACT PLATING	4.PIN TYPE	5.INSULATOR COLOR
SINGLE ROW 1*4 - 1*24	A: BRASS B: PHOSPHOR BRONZE	T: TIN PLATED S: SELECTIVE G: GOLD FLASH A: 5u" INCH GOLD B: 10u" INCH GOLD C: 15u" INCH GOLD D: 30u" INCH GOLD	A: 0.6*0.4mm B: 0.64*0.64mm	1. BLACK

