

B63 FEMALE HEADER WITH POLARIZATION KEY STR (H: 4.5mm)

PITCH: 2.0mm * 2.0mm




SPECIFICATIONS

Material




Insulator : Nylon 66, glass reinforced, rated UL 94V-0
Contact : Phosphor Bronze

Electrical

Current Rating : 1 Amp
Contact Resistance : 30 mΩ max.
Insulation Resistance : 3000 MΩ min.
Dielectric Withstanding Voltage : 500V AC for 1minute
Operating Temperature : -40°C to +105°C
▶ Mating Suggestion : C78, C79 & C80 series.



POSITION	A	B	C
4	4.55	2.00	--
6	6.55	4.00	--
8	8.55	6.00	--
10	10.55	8.00	--
12	12.55	10.00	--
14	14.55	12.00	2.00
16	16.55	14.00	2.00
18	18.55	16.00	2.00
20	20.55	18.00	2.00
22	22.55	20.00	2.00
24	24.55	22.00	2.00
26	26.55	24.00	2.00
28	28.55	26.00	2.00
30	30.55	28.00	2.00
32	32.55	30.00	2.00
34	34.55	32.00	2.00
36	36.55	34.00	2.00
38	38.55	36.00	2.00
40	40.55	38.00	2.00
42	42.55	40.00	2.00
44	44.55	42.00	2.00
46	46.55	44.00	2.00
48	48.55	46.00	2.00
50	50.55	48.00	2.00
68	68.55	66.00	2.00



RECOMMENDED P.C.B LAYOUT

How to order: B63 - 1 - 2 - 3 - 4 - G(RoHS)

1.NO. OF CONTACT	2.CONTACT MATERIAL	3.CONTACT PLATING	4.INSULATOR COLOR
04 06 08 10 12 14 16 18 20 22 24 26 28 30 32 34 36 38 40 42 44 46 48 50 68	A: PHOSPHOR BRONZE	T: TIN PLATED S: SELECTIVE G: GOLD FLASH A: 5u" INCH GOLD B: 10u" INCH GOLD C: 15u" INCH GOLD D: 30u" INCH GOLD	1. BLACK



DON CONNEX
ELECTRONICS CO., LTD

T:886 2 86483356 | F:886 2 86485885
e-mail: info@donconnex.com.tw



Connector:E163339 | Flat cable:E162690
Wiring Harnesses:E312257