

B54 SINGLE ROW FEMALE HEADER DUAL ENTRY SMT (H: 7.0mm)

PITCH: 2.54mm

SPECIFICATIONS

Material

Insulator : LCP, glass reinforced, rated UL 94V-0

Contact : Phosphor Bronze

Electrical

Current Rating : 1 Amp







Contact Resistance : 30 mΩ max.

Insulation Resistance : 3000 MΩ min.


Dielectric Withstanding Voltage : 500V AC for 1minute

Operating Temperature : -40°C to +105°C

► Mating Suggestion : C15, C16, C19 & C23 series.



RECOMMENDED TOP ENTRY P.C.B LAYOUT



RECOMMENDED DUAL ENTRY P.C.B LAYOUT

How to order: B54 - 1 - 2 - 3 - 4 - 5 - G(RoHS)

1.NO. OF CONTACT	2.CONTACT MATERIAL	3.CONTACT PLATING	4.PACKAGING	5.INSULATOR COLOR
SINGLE ROW 1*2 - 1*40	B: PHOSPHOR BRONZE	T: TIN PLATED S: SELECTIVE G: GOLD FLASH A: 5u" INCH GOLD B: 10u" INCH GOLD C: 15u" INCH GOLD D: 30u" INCH GOLD	A:TUBE WITH PAD B: TUBE W/O PAD C: TAPE & REEL WITH PAD	9. IVORY

